

## REFERENCES

1. Morent R, De Geyter N, Verschuren J, De Clerck K, Kiekens P, Leys C. Non-Thermal Plasma Treatment of Textiles. *Surface & Coatings Technology* 2008; 202, 14: 3427-3449.
2. Hyun JH. A new approach to characterize crystallinity by observing the mobility of plasma treated polymer surfaces. *Polymer* 2001; 42, 6473 – 6477.
3. Marais S, Metayer M, Poncin-Epaillard F. Effect of a plasma treatment on water diffusivity and permeability of an unsaturated polyester resin. *J. Fluorine Chem.* 2001; 107: 199 – 203.
4. Gonzales AR, Schofield RB, Hart SV. Third Status Report to the Attorney General on Body Armor Safety Initiative Testing and Activities, 24.08.2005, U.S. Department of Justice Office of Justice Programs, National Institute of Justice; [http://www.ojp.usdoj.gov/bvpbasi/docs/SupplementII\\_08\\_12\\_05.pdf?popupWindow=Y](http://www.ojp.usdoj.gov/bvpbasi/docs/SupplementII_08_12_05.pdf?popupWindow=Y) [2014-01-30].
5. MacManus LF, Walzar MJ, McIntyre NS. Study of ultraviolet light and ozone surface modification of polypropylene. *J. Polym. Sci. Polym. Chem.* 1999; 37: 2489-2501.
6. Oosterom R, Ahmed TJ, Poulis JA, Bersee HEN. Adhesion performance of UHMWPE after different surface modification techniques. *Medical Engineering & Physics* 2006; 28: 323-330.
7. Shi X, Wang Q, Xu L, Ge S, Wang Ch. Hydrogenated diamond-like carbon film deposited on UHMWPE by RF-PECVD. *Appl. Surf. Sc.* 2009; 255: 8246-8251.
8. Liu H, Pei Y, Xie D, Deng X, Leng YX, Jin Y, Huang N. Surface modification of ultra-high molecular weight polyethylene (UHMWPE) by argon plasma. *Appl. Surf. Sci.* 256, 2010, 3941-3945.
9. Huang Y, Economy J. Wear properties of UHMWPE/aromatic thermosetting copolyester blends in unlubricated sliding. *Wear* 2007; 262: 943-948.
10. Li CX, Bell T. Potential of plasma nitriding of polymer for improved hardness and wear resistance. *Journal of Materials Processing Technology* 2005; 168, 2: 219-224; doi:10.1016/j.jmatprotec.2004.10.018.
11. Ohta M, Hyon SH, Oka M. Wear resistance of lightly cross linked ultrahigh-molecular-weight polyethylene crystalized form the melt under uniaxial compression. *Wear* 1999; 225-229, 312-318.
12. Ge S, Wang Q, Zhang D, Zhu H, Xiong D, Huang Ch, Huang X. Friction and wear behavior of nitrogen ion implanted UHMWPE against ZrO<sub>2</sub> ceramic. *Wear* 2003; 255: 1069-1075.
13. Shi W, Li XY, Dong H. Improved wear resistance of ultra-high molecular weight polyethylene by plasma immersion ion implantation. *Wear* 2001; 250: 544-552.
14. Xiong D, Gao Z, Jin Z. Friction and wear properties of UHMWPE against ion implanted titanium alloy. *Surface & Coatings Technology* 2007; 201: 6847-6850.
15. Shi X, Wang Q, Xu L, Ge S, Wang Ch. Hydrogenated diamond-like carbon film deposited on UHMWPE by RF-PECVD. *Appl. Surf. Sc.* 2009; 255: 8246-8251.

16. Struszczyk MH, Puszkarz AK, Wilbik-Hałgas B, Cichecka M, Litwa P, Urbaniak-Domagała W, Krucinska I. The surface modification of ballistic textiles using plasma-assisted chemical vapor deposition (PACVD). *Textile Research Journal* **in press**
17. Fejdyś M, Łandwijt M, Struszczyk MH. Effect of Accelerated Ageing Conditions on the Degradation Process of Dyneema® Polyethylene Composites. *Fibres & Textiles in Eastern Europe* 2011; 19, 1(84): 60-65.
18. Struszczyk MH, Gutowska A, Palys B, et al. Accelerated Ageing of the Implantable, Ultra-Light, Knitted Medical Devices Modified by Low-Temperature Plasma Treatment - Part 1. Effects on the Physical Behaviour. *Fibres & Textiles in Eastern Europe* 2012; 20, 6B: 121-127.
19. Kucharska M, Struszczyk MH, Cichecka M, et al. Prototypes of Primary Wound Dressing of Fibrous and Quasi-Fibrous Structure in Terms of Safety of Their Usage. *Fibres & Textiles in Eastern Europe* 2012; 20, 6B: 142-148.
20. Redlich G, Fortuniak K. *Tworzywa Sztuczne i Chemia* 2010; 3: 8.