

References

1. Li Q, Hurren CJ, Ding C, Wang L, Lin T and Wang X. Ultrasonic scouring of wool and its effects on fibre breakage during carding. *Journal of The Textile Institute* 2011; 102: 1059–1064.
2. Żyłła R, Sójka-Ledakowicz J, Michalska K, Kos L and Ledakowicz S. Effect of UV/H₂O₂ on Fouling in Textile Wastewater Nanofiltration. *Fibres and Textiles in Eastern Europe* 2012; 20, 1(90): 99-104.
3. Koh J. Alkali-hydrolysis kinetics of alkali-clearable azo disperse dyes containing a fluorosulphonyl group and their fastness properties on pet/cotton blends. *Dyes and Pigments* 2005; 64: 17–23.
4. Burkinshaw SM and Kabamb O. Attempts to reduce water and chemical usage in the removal of reactive dyes: Part 1 bis(aminochlorotriazine) dyes. *Dyes and Pigments* 2009; 83: 363-374.
5. Blanchard E J. Dye ability of cross linked cationic cotton fabrics. *Textile Chemist & Colourist* 1988; 20: 25-29.
6. Moussa A, Ghali AE, Ellouzi S and Sakli F. Colour and fastness study of wool dyeing in multiple reuse dye baths using acid and reactive dyestuffs in laboratory scale. *The Journal of the Textile Institute* 2013; 104: 260–269.
7. Mughal JM, Naeem M, Aleem A, Saeed R and Ahmed K. Effect of a cationising agent on the conventional reactive dyeing of cotton. *Coloration Technology* 2008; 124: 62-65.
8. Haas J, Koenemund B and Vogt U. New and better way to wash-off reactive dyestuffs. *Melliand International* 2000; 6: 243-244.
9. Dvarioniene J, Stasiskiene Z and Knudsen HH. Pilot-scale membrane filtration study on water reuse of rinsing water after reactive cotton dyeing. *Environmental Research Engineering and Management* 2005; 3: 3-10.
10. Burkinshaw SM and Katsarelias D. A study of the wash-off and aftertreatment of dichlorotriazinyl reactive dyes on cotton. *Dyes and Pigments* 1995; 29: 139-153.
11. Burkinshaw SM and Katsarelias D. The wash-off of reactive dyes on cellulosic fibres. Part 4: The use of different alkalis with monochlorotriazinyl dyes on cotton. *Dyes and Pigments* 1997; 35: 249-259.
12. Akcakoca EP, OZguney AT and Atav R. The efficiency of washing agents in the post-dyeing removal of hydrolyzed reactive dye. *Dyes and Pigments* 2007; 72: 23-27.
13. Shaikh IA, Ahmad N and Urooj F. A novel method to improve color fastness of deep shade reactive dyeing using ozone in washing off. *AATCC Review* 2010; 10: 73–77.
14. Akalin M, Merdan N, Kocak D. Effects of ultrasonic energy on the wash fastness of reactive dyes. *Ultrasonics* 2004; 42:161–164.
15. Suwanruji P and Freeman HS. Design, synthesis and application of easy wash-off reactive dyes. *Coloration Technology* 2006; 122: 27–36.
16. Verma AK, Dash RR and Bhunia P. A review on chemical coagulation/flocculation technologies for removal of colour from textile wastewaters. *Journal of Environmental Management* 2012; 93: 154-168.
17. Anjaneyulu Y, Chary NS and Raj DSS. Decolourization of industrial effluents available methods and emerging technologies-A Review. *Reviews in Environmental Science and Biotechnology* 2005; 4: 245-273.
18. Golob V, Vinder A and Simonic M. Efficiency of coagulation/flocculation method for treatment of dye bath effluents. *Dyes and Pigments* 2005; 67: 93-97.
19. Papic S, Koprivanac N and Bozic AL. Removal of reactive dyes from wastewater using Fe(III) coagulant. *Coloration Technology* 2000; 161: 352–358.
20. Kim TH, Park C, Shin EB and Kim S. Decolourization of disperse and reactive dyes by continuous electrocoagulation process. *Desalination* 2002; 150: 165–175.

21. Georgiou D, Aivazidis A, Hatiras J and Gimouhopoulos K. Treatment of cotton textile wastewater using lime and ferrous sulfate. *Water Research* 2003; 37: 2248–2250.
22. Errais E, Duplay J and Darragi F. Textile dye removal by natural clay – Case study of Fouchana Tunisian clay. *Environmental Technology* 2010; 31: 373-38.
23. Wong PW, Teng TT, Rahman NA and Norulaini N. Efficiency of the Coagulation-Flocculation method for the treatment of dye mixtures containing disperse and reactive dye. *Water Quality Research Journal of Canada* 2007; 42:13-20.
24. Duan J and Gregory J. Coagulation by hydrolyzing metal salts. *Advances in Colloid and Interface Science* 2003; 100: 475–502.
25. Tan BJ, Teng TT and Omar AK. Removal of dyes and industrial dye wastes by magnesium chloride. *Water Research* 2000; 34: 597-601.
26. Ooi PY, Teng TT, Omar AKM and Norulaini NAR. Removal of dyes by aqueous mixed coagulants. *ASEAN Journal of Chemical Engineering* 2005; 5: 52-64.
27. Canizares P, Jiménez C, Martínez F, Rodrigo MA and Sáez C. The pH as a key parameter in the choice between coagulation and electrocoagulation for the treatment of wastewaters. *Journal of Hazardous Materials* 2009; 163: 158–164.