References

- 1. Dunlop J I. On the compression characteristics of fiber masses. *J. Textile Institute* 1983; 74, 92-7.
- 2. Carnaby G A and Pan N. Theory of the compression hysteresis of fibrous assemblies. *Textile Res.* J. 1989; 59: 275-84.
- 3. Beil N B and Roberts W W Jr. Modeling and computer simulation of the compressional behaviour of fiber assemblies, Part I: comparison to van Wyk's theory. *Textile Res. J.* 2002; 72,4: 341-51.
- 4. Hu J and Newton A. Low-load lateral-compression behaviour of woven fabrics. *Journal of Textile Institute* 1997; 88, Part I, 3: 242-253.
- 5. Matsudaira M and Hong Q. Features and characteristic values of fabric compressional curves. *International Journal of Clothing Science and Technology* 1994; 6, 2/3: 37-43.
- 6. Zajączkowski J. Impact of an Object on a Layer of Fibres Submerged in a Fluid. *Fibres and Textiles in Eastern Europe* 2010, 18, 6(83): 60-62.
- 7. Zajączkowski J. Resonance Vibrations of an Elastic System Supported on a Textile Layer. *Fibres and Textiles in Eastern Europe* 2014; 22, 2(104): 76-79.
- 8. Knight D W. An Introduction to the Art of Solenoid Inductance Calculation with emphasis on radio-frequency applications. http://g3ynh.info/zdocs/magnetics/Solenoids.pdf
- 9. Lu H, Pillans B, Lee J-B and Jonsson E. Micromachined On-Chip High-Aspect Ratio Air Core Solenoid Inductor for Multi-GHz Applications. School of Engineering and Computer Science University of Texas at Dallas, Richardson. Microwave Symposium Digest, 2004 IEEE MTT-S International (Volume: 2).
- 10. Schauber M J, Newman S A, Goodman L R, Suzuki I S and Suzuki M. Measurement of mutual inductance from the frequency dependence of impedance of AC coupled circuits using a digital dual-phase lock-in amplifier. *American Journal of Physics* 2008; 76: 129.
- 11. Zajączkowski J. Machine Mechanics, available at https://sites.google.com/site/occupationsafe/