

References

1. Wang XC, Liu Z, Zhou Z, He Q, Zeng HX. Automatic identification of gray porosity and its influence on shielding effectiveness for electromagnetic shielding fabric. *Int. J. Cloth. Sci. Tech.* 2014; 26(5):424-436.
2. Liu Z, Wang XC, Zhang YH, Zhou Z. Analysis of surface metal fiber arrangement of electromagnetic shielding fabric and its influence on shielding effectiveness. *Int. J. Cloth. Sci. Tech.* 2016; 28(2):191-200.
3. Liu Z, Rong X, Zheng QX, Sun RL, Chen YN, Wang XC. Analysis of arrangement structure for metal fiber in blended electromagnetic shielding fabric, *2014 Progress in Electromagnetics Research Symposium (PIERS 2014)*, Aug.25-28.
4. Kazantseva NE, Ponomarenko AT, Shevchenko VG, Klason C. Magnetically textured composite materials as elements of electromagnetic wave absorbers. *Electromagnetics* 2000; 20(6):453-466.
5. Ortlek HG, Saracoglu OG, Saritas O. Electromagnetic shielding characteristics of woven fabrics made of hybrid yarns containing metal wire. *Fiber. Polym.* 2012; 13(1):63-67.
6. Wang X, Liu Z, Zhou Z. Rapid computation model for accurate evaluation of electromagnetic interference shielding effectiveness of fabric with hole based on equivalent coefficient. *Int. J. Appl. Electrom.* 2015; 47(1):177-185.
7. Li R, Zhang L, Jia L. Influence of fabric structural model on shielding effectiveness of electromagnetic radiation shielding fabric. *Int. J. Model. Ident. Contr.* 2010; 11(3/4):211-217.
8. Liu Z, Wang XC. Influence of fabric weave type on the effectiveness of electromagnetic shielding woven fabric. *J. Electro. Magnet. Wave.* 2012; 26(14/15):1848-1856.
9. Saini P, Choudhary V. Conducting polymer coated textile based multilayered shields for suppression of microwave radiations in 8.2–12.4 GHz range. *J. Appl. Polym. Sci.* 2013; 129(5):2832–2839.
10. Wang XC, Liu Z, Zhou Z. Virtual metal model for fast computation of shielding effectiveness of blended electromagnetic interference shielding fabric. *Int. J. Appl. Electrom.* 2014; 44(1):87-97.
11. Araneo R, Lovat G. Analysis of the shielding effectiveness of metallic enclosures excited by internal sources through an efficient Method-of-Moment approach. *Appl. Comput. Electrom.* 2010; 25(7):600-611.
12. Liu Z, Zhang YH, Rong X, Wang XC. Influence of metal fibre content of blended electromagnetic shielding fabric on shielding effectiveness considering fabric weave. *Fibres. Text. East. Eur.* 2015; 23(4): 83-87.
13. Saravanja B, Malaric K, Pusic T, Ujevic D. Impact of dry cleaning on the electromagnetic shield characteristics of interlining fabric. *Fibres. Text. East. Eur.* 2015; 23(1):104-108.
14. Wang XC, Liu Z. Influence of fabric density on shielding effectiveness of electromagnetic shielding fabric. *Prz. Elektrotechniczny* 2012; 88(11a):236-238.
15. Ching IS, Jin TC. Effect of stainless steel-containing fabrics on electromagnetic shielding effectiveness. *Textile Res. J.* 2004; 74(1):51-54.
16. Liu Z, Wang XC. Manufacture and performance evaluation of solar garment. *J. Clean Prod.* 2013; 42:96-102.
17. Koprowska J, Dobruchowska E, Reszka K, Szwugier A. Morphology and electromagnetic shielding effectiveness of PP nonwovens modified with metallic layers. *Fibres. Text. East. Eur.* 2015; 23(5):84-91.
18. Wang XC, Li XJ. Recognition of fabric density with quadratic local extremum. *Int. J. Cloth. Sci. Tech.* 2012; 24(5):328-338.
19. Liu Z, Wang XC. Relation between shielding effectiveness and tightness of electromagnetic shielding fabric. *J. Ind. Text.* 2013; 43(2):302-316.
20. Liu Z, Rong X, Yang YL, Wang XC. Influence of Metal Fiber Content and Arrangement on Shielding Effectiveness for Blended Electromagnetic Shielding Fabric. *Mater. Sci-medzg.* 2015; 21(2):265-270.
21. Qian ZM, Chen ZJ. Electromagnetic compatibility design and interference suppression technology. Ed. *Zhejiang University Press, Hangzhou, 2000.*
22. Liu Z., Su Y., Li YP, Pan Z, Wang XC. Numerical calculation of shielding effectiveness of electromagnetic

shielding fabric based on finite difference time domain. *Int. J. Appl. Electrom.* 2016;50(4):593-603.