

## References

1. Sarıdağ S, Helvacıoğlu-Yiğit D, Özcan M, et al. Micro-computerized tomography analysis of cement voids and pull-out strength of glass fiber posts luted with self-adhesive and glass-ionomer cements in the root canal[J]. *J. Adhes. Sci. Technol.* 2016; 30(14): 1585-1595.
2. Huang Y, Jiang M, Xu M, et al. Curing behavior and processability of BMI/3 - APN system for advanced glass fiber composite laminates[J]. *J. Appl. Polym. Sci.* 2016; 133(27): 43640.
3. Munawar M A, Khan S M, Gull N, et al. Fabrication and characterization of novel zirconia filled glass fiber reinforced polyester hybrid composites[J]. *J. Appl. Polym. Sci.* 2016; 133(27): 1-9.
4. Kulkova J, Moritz N, Huhtinen H, et al. Bioactive glass surface for fiber reinforced composite implants via surface etching by Excimer laser[J]. *Med. Eng. Phys.* 2016; 38(7): 664-670.
5. Mastali M, Dalvand A, Sattarifard A R. The impact resistance and mechanical properties of reinforced self-compacting concrete with recycled glass fibre reinforced polymers[J]. *J. Clean. Prod.* 2016; 124: 312-324.
6. Betanzos F B, Gimeno-Fabra M, Segal J, et al. Cyclic pressure on compression-moulded bioresorbable phosphate glass fibre reinforced composites[J]. *Mater. Design.* 2016; 100: 141-150.
7. Nam S, Lee D, Kim J. Development of a fluoroelastomer/glass fiber composite flow frame for a vanadium redox flow battery (VRFB)[J]. *Compos. Struct.* 2016; 145: 113-118.
8. Vazquez-Zuniga L A, Feng X, Kwon Y, et al. W-type highly erbium-doped active soft-glass fibre with high nonlinearity[J]. *Electron. Lett.* 2016; 52(12): 1047-1048.
9. Rippe M P, Wandscher V F, Bergoli C D, et al. Effect of the frequency of mechanical pulses for fatigue aging testing on push-out bond strength between glass fiber posts and root dentin[J]. *J. Adhes. Sci. Technol.* 2016; 30(11): 1243-1252.
10. Feo L, Luciano R, Misseri G, et al. Irregular stone masonries: Analysis and strengthening with glass fibre reinforced composites[J]. *Compos. Part B: Eng.* 2016; 92: 84-93.
11. Ibáñez-Gutiérrez F T, Cicero S, Carrascal I A, et al. Effect of fibre content and notch radius in the fracture behaviour of short glass fibre reinforced polyamide 6: An approach from the Theory of Critical Distances[J]. *Compos. Part B: Eng.* 2016; 94: 299-311.
12. Nicholas J, Mohamed M, Dhaliwal G S, et al. Effects of accelerated environmental aging on glass fiber reinforced thermoset polyurethane composites[J]. *Compos. Part B: Eng.*

2016; 94: 370-378.

13. Li D, Xu W, Kuan P, et al. Spectroscopic and laser properties of Ho<sup>3+</sup> doped lanthanum - tungsten - tellurite glass and fiber[J]. *Ceram. Int.* 2016; 42(8): 10493-10497.
14. Tavanai H, Morshed M, Hosseini S M. Effects of on-line melt blending of polypropylene with polyamide 6 on the bulk and strength of the resulting BCF yarn[J]. *Iran. Polym. J.* 2003; 12: 421-430.
15. Jiang Y, Wang S Y. Characterization & EIB testing of the bulking property of yarn[J]. *J. Donghua Univ.* 2007; 33: 760-763.
16. Shaikhzadeh Najar S, Etrati S M, Seyed-Esfahani M H, et al. The effect of blend ratios of unrelaxed and relaxed acrylic fibres on physical properties of high-bulk worsted yarns[J]. *J. Text. I.* 2005; 96(5): 311-318.
17. Wang R, Gao Y, Zong Y, et al. Testing and Discussion on the Morphology and Bulk of the Textured Yarn by EIB[J]. *J. Donghua Univ.* 2004; 30(5): 65-68.
18. Sadeghi-Sadeghabad M, Tavakoli M, Alamdar-Yazdi A, et al. Coincident optimization of specific volume and tensile strength at acrylic high-bulked yarn using Taguchi method[J]. *J. Text. I.* 2015; 106(12): 1328-1337.
19. Yang S, Li L, Xiao T, et al. Role of surface chemistry in modified ACF (activated carbon fiber)-catalyzed peroxyomonosulfate oxidation[J]. *Appl. Surf. Sci.* 2016; 383: 142-150.
20. Fu Z, Liu B, Deng Y, et al. The suitable itaconic acid content in polyacrylonitrile copolymers used for PAN - based carbon fibers[J]. *J. Appl. Polym. Sci.* 2016; 133(38): 1-10.
21. Xia L, Zhang T, Chai Z, et al. Effect of boron doping on fracture behavior of carbon fiber reinforced lithium aluminosilicate glass ceramics matrix composites[J]. *J. Eur. Ceram. Soc.* 2016; 36: 3513-3522.
22. Liu B, Wang H, Chen Y, et al. Pt nanoparticles anchored on Nb<sub>2</sub>O<sub>5</sub> and carbon fibers as an enhanced performance catalyst for methanol oxidation[J]. *J. Alloys Compd.* 2016; 682: 584-589.
23. Sun H, Memon S A, Gu Y, et al. Degradation of carbon fiber reinforced polymer from cathodic protection process on exposure to NaOH and simulated pore water solutions[J]. *Mater. Struct.* 2016; 49: 5273-5283.
24. Dong K, Liu K, Zhang Q, et al. Experimental and numerical analyses on the thermal conductive behaviors of carbon fiber/epoxy plain woven composites[J]. *Int. J. Heat Mass Tran.* 2016; 102: 501-517.

25. Sha J J, Li J, Wang S H, et al. Improved microstructure and fracture properties of short carbon fiber-toughened ZrB<sub>2</sub>-based UHTC composites via colloidal process[J]. *Int. J. Refract. Met. H.* 2016; 60: 68-74.
26. Rodríguez-Uicab O, Avilés F, Gonzalez-Chi P I, et al. Deposition of carbon nanotubes onto aramid fibers using as-received and chemically modified fibers[J]. *Appl. Surf. Sci.* 2016; 385: 379-390.
27. Salazar P, Martín M, O'Neill R D, et al. Glutamate microbiosensors based on Prussian Blue modified carbon fiber electrodes for neuroscience applications: In-vitro characterization[J]. *Sensor Actuat. B: Chem.* 2016; 235: 117-125.
28. Du B, Hong C, Zhou S, et al. Multi-composition coating for oxidation protection of modified carbon-bonded carbon fiber composites[J]. *J. Eur. Ceram. Soc.* 2016; 36: 3303-3310.
29. Liu Y J, Zhao X M, Tuo X. A study on the performance of the air textured yarn of glass fiber[J]. *J. Funct. Mater.* 2016; 47(1): 1082-1086.
30. Liu Y J, Zhao X M, Li W B, et al. A Study on the Performance of Fancy Bulk Yarn of Glass Fiber[J]. *J. Silk* 2015; 1(52): 5-16.
31. Tavanai H, Morshed M, Moghaddam A. Production of high bulk polyester filament yarn[J]. *J. Text. I.* 2013; 104(1): 1-6.
32. Liu L, Tian B, Sun W R, et al. Bright-dark vector soliton solutions for a generalized coupled Hirota system in the optical glass fiber[J]. *Commun. Nonlinear Sci.* 2016; 39: 545-555.