

References

1. Barton J, Niemczyk A, Czaja K, Korach Ł, Sacher-Majewska B. Polymer composites, biocomposites and nanocomposites. Production, composition, properties and application fields. *Chemik* 2014; 68, 4: 280-287.
2. Etteyeb N, Jaouen V, Steunou N, Gharbi N, Coradin T. Elaboration, Stability and Enzymatic Degradation of Hydroxypropylcellulose/Polysiloxane Biocomposite Membranes. *Silicon* 2012; 4, 1: 79-84.
3. Sahari J, Salit MS, Zainudin ES, Maleque MA. Degradation Characteristics of SPF/SPS Biocomposites. *FIBRES & TEXTILES in Eastern Europe* 2014; 22, 5(107): 96-98.
4. Wan YZ, Luo H, He F, Liang H, Huang Y, Li XL. Mechanical, moisture absorption, and biodegradation behaviours of bacterial cellulose fibre-reinforced starch biocomposites. *Compos. Sci. Technol* 2009; 69: 1212-17.
5. Reddy TRK, Kim HJ, Park JE. Composites from renewable and sustainable materials. *Renewable Biocomposite Properties and their Applications* 2016; 10: 177-197.
6. Prochoń M, Janowska G, Przepiórkowska A, Kucharska – Jarząbek A. Thermal stability and flammability of biodecomposable elastomer materials. *Polimery* 2013; 58: 413-420.
7. Martikka O, Huuhilo T, Butylina S, Karki T. The effect of mineral fillers on the thermal properties of wood-plastic composites. *Wood Material Science & Engineering* 2012; 7, 2: 107-114.
8. Hartikainen J, Lindner M, Harmia T, Friedrich K. Mechanical properties of polypropylene composites reinforced with long glass fibres and mineral follers. *Plastics, Rubber and Composites, Macromolecular Engineering* 2004; 33, 2-3: 77-84.
9. Mandal M, Maji TK. Preparation, physical properties and ultraviolet resistance of wood nanocomposites based on modified soybean oil and bentonite. *Wood Material Science & Engineering*. 2018; <https://doi.org/10.1080/17480272.2018.1463289>.
10. Chen Y, Guan J, Hu H, Gao H, Zhang L. Structural change and interfacial interaction in blended rubber composites filled with silica–kaolin hybrid fillers. A Fourier transform infrared spectroscopic study. *Spectroscopy Letters. An International Journal for Rapid Communication*. 2016; 49, 2: 118-127.
11. Jastrzębska M. Wpływ nanonapełniacza na wybrane właściwości kompozytów z recyklem poliestrowo-szklanym. *Inż. Ap. Chem.* 2012; 51, 3: 63-64.
12. Ławińska K, Gendaszewska D, Kozar O, Sprynsky M, Wionczyk B. Studies on selected properties of natural mineral modified leathers with the addition of polyhexamethylenebiguanide-based preparation. *Technologia i Jakość Wyrobów* 2017; 62: 86-95.
13. Okada A, Kawasumi M, Usuki A, Kojima Y, Karauchi T, Kamiagaito O. Nylon 6-clay hybrid. *Materials Research Society* 1989; 171: 45-50.
14. Suberlyak OV, Krasinskyi VV, Moravskyi VV, Gerlach H, Jachowicz T. Influence of aluminosilicate filler on the physiomechanical properties of polypropylene polycaproamide composites. *Materials Science* 2014; 50(2): 296-302.
15. Mittal V. Polypropylene – layered silicate nanocomposites: filler matrix interactions and mechanical properties. *Journal of Thermoplastic Composite Materials* 2007; 20(6): 575-599.
16. Błędzki AK, Jaszkiewicz A, Urbaniak M, Stankowska-Walczak D. Biocomposites in the Past and in the Future. *FIBRES & TEXTILES in Eastern Europe* 2012; 20 6B(96): 15-22.
17. Wieczorek-Ciurowa K, Famielec S, Fela K, Woźny Z. The process of waste incineration in the tanning industry. *Chemik* 2011; 65(10): 917-922.
18. Fela K, Wieczorek-Ciurowa K, Konopka M, Woźny Z. Present and prospective leather industry waste disposal. *Polish Journal of Chemical Technology* 2011; 13: 53-55.
19. Materials Data Book. Cambridge University Engineernig Departament. Edition 2003.

20. Wyszomirski P, Lewicka E. Bentonite as a versatile industrial mineral for different markets. *Gospodarka Surowcami Mineralnymi* 2005; 21(3): 5-19.
21. Jonczy I, Borówka B. Characteristics of near-surface part of the Orzesze beds in the region of the main saddle in view of weathering processes. *Mineral Resources Management* 2016; 32(2): 111-124.
22. Góralczyk S, Kukielska D. The quality of Polish aggregates. *Górnictwo i Geoinżynieria* 2010; 34(4): 211-224.
23. Szczerba J, Prorok R, Goławski C, Madej D, Śnieżek E. Effect of selected ecological coal-tar pitches on the properties of dolomite refractories. *Materiały Ceramiczne* 2011; 63(4):779-785.
24. Falkiewicz-Dulik M. Characteristics of the materials used in the insoles. *Technologia i Jakość Wyrobów* 2016; 61: 86-94.
25. Serweta W, Olejniczak Z, Woźniak B. Analysis of insole material impact on comfort during physical exertion. *FIBRES & TEXTILES in Eastern Europe*. 2018; 26, 2(128): 100-103. DOI: 10.5604/01.3001.0011.5746.
26. Marszałek A. Zagrożenie zimnym środowiskiem w aspekcie wieku pracownika i parametrów odzieży ciepłochronnej. *Bezpieczeństwo Pracy: Nauka i Praktyka* 2012; 8: 20-23.
27. Juruć A, Kubiak M, Wierusz-Wysocka B. Psychological and medical problems in prevention and treatment of eating disorders among people with type 1 diabetes. *Clin Diabet* 2016; 5(1): 26-31.
28. Irzmańska E. Footwear use at workplace and recommendations for the improvement of its functionality and hygiene. *Autex Research Journal* 2014; 14 (2): 89-94.
29. Irzmańska E, Dutkiewicz J, Irzmański R. New approach to assesing comfort of use of protective footwear with a textile liner and its impact on foot physiology. *Textile Research Journal* 2014. 87(7): 728-738.
30. Wrześniowska-Tosik K, Wawro D, Stęplewski W, Szadkowski M. Fibrous products with keratin content. *FIBRES & TEXTILES in Eastern Europe* 2007; 15, 2(61): 30-35.
31. Wrześniowska-Tosik K, Wawro D, Ratajska M, Stęplewski W. Novel biocomposites with feather keratin. *FIBRES & TEXTILES in Eastern Europe* 2007; 15, 5-6: 64-65.
32. Wrześniowska-Tosik K, Kucharska M, Wawro D. Fibrous keratin-containing composite. *FIBRES & TEXTILES in Eastern Europe* 2008; 16, 6(71): 113-116.