

## References:

1. Lee SJ, Jeong SJ, Kim WS. Numerical design of the diesel particulate filter for optimum thermal performances during regeneration. *Applied Energy* 2009; 86: 1124-1135.
2. Frank B, Schlogl R, Su DS. Diesel soot toxification. *Environmental Science Technology* 2013; 47: 3026-3027.
3. Benaqqa C, Gomina M, Beurotte A, Boussuge M, Delattre B, Pajot K, Pawlak E, Rodrigues F. Morphology, physical, thermal and mechanical properties of the constitutive materials of diesel particulate filters. *Applied Thermal Engineering* 2014; 62: 599-606.
4. Tsuneyoshi K, Hayama S. A new SiC-based DPF for the Automotive Industry. In: *DEER Conference*, 6 August 2008, pp. 1-14 Corporation, Dearborn, Michigan.
5. Stamatellou AM, Stamatelos A. Overview of Diesel particulate filter systems sizing approaches. *Applied Thermal Engineering* 2017; 121: 537-546.
6. Bueno-López A. Diesel soot combustion ceria catalysts. *Applied Catalysis B Environmental* 2014; 146: 1-11.
7. Burch R. Knowledge and know-how in emission control for mobile applications. *Catalysis Review* 2004; 46: 271-334.
8. ASTM D1777-96: 2015. Standard Test Method for Thickness of Textile Materials, ASTM International, West Conshohocken, PA.
9. Jaksic D, Jaksic N. Porosity of the flat textiles. *Woven Fabric Engineering*, Sciyo: 2010, pp. 255-272.
10. BS 5636: 1990. Method of test for the determination of the permeability of fabrics to air, British Standards, London, England.
11. ASTM D5035-11: 2015. Standard Test Method for Breaking Force and Elongation of Textile Fabrics (Strip Method), ASTM International, West Conshohocken, PA.
12. ASTM D3786 / D3786M-18: 2018. Standard Test Method for Bursting Strength of Textile Fabrics—Diaphragm Bursting Strength Tester Method, ASTM International, West Conshohocken, PA.
13. Lee C. Heat transfer of fibrous insulation battings. Army Natick Research and Development Command technical report/TR-84/055, USA, May 1984.
14. Gibson PW, Lee C, Frank K. Application of nano fiber technology to nonwoven thermal insulation. *Journal of Engineered Fibers and Fabrics* 2007; 2: 32-40.

15. Zakriya GM, Ramakrishnan G, Palani Rajan T, Abinaya D. Study of thermal properties of jute and hollow conjugated polyester fibre reinforced non-woven composite. *Journal of Industrial Textiles* 2017; 46: 1393-1411.
16. Mahmood N, Yuan Z, Schmidt J, Xu CC. Depolymerization of lignins and their applications for the preparation of polyols and rigid polyurethane foams: A review. *Renewable and Sustainable Energy Reviews* 2004; 60: 317-329.
17. BS 6993: 1989. Thermal and radiometric properties of glazing. Part 1: method of calculation of steady state U value.
18. Dos Santos WN, Mummery P, Wallwork A. Thermal diffusivity of polymers by the laser flash technique. *Polymer Testing* 2005; 24: 628–634.
19. Konstandopoulos AG, Kostoglou M, Skaperdas E, Papaioannou E, Zarvalis D, Kladopoulou E. Fundamental studies of diesel particulate filters: transient loading, regeneration and aging. *SAE paper* 2000; 1: 1016-1023.
20. Deusdle T, Janoske U, Piesche M. A CFD-model describing filtration, regeneration and deposit rearrangement effects in gas filter systems. *Chemical Engineering Journal* 2008; 135: 49-55.
21. Adler J. Ceramic diesel particulate filters. *International Journal of Applied Ceramic Technology* 2005; 2: 429-439.
22. Sakka S, Kamiya K. The sol-gel transition in the hydrolysis of metal alkoxides in relation to the formation of glass fibers and films. *Journal of Non Crystalline Solids* 1982; 48: 31-46.
23. Martin JR, Lamb GE. Measurement of thermal conductivity of nonwovens using a dynamic method. *Textile Research Journal* 1987; 57: 721-727.