

## References

1. Mao N et al. Characteristics Of Fabric-To-Fabric Self-Friction Properties. *In: The 90th Textile Institute World Conference*, 25-28 Apr 2016, Poznan, Poland.
2. Moses JJ1, Venkataraman. Study of Mechanical and Surface Properties on some Chemical Treated Cotton Fabric by KES-F, SEM and FTIR Analysis, Department of Applied Science, PSG College of Technology, Coimbatore, India.
3. Czaplicki Z, Matyjas-Zgondek E, Serweta W. Directions of the Finishing of Fibres and Textile Development. *FIBRES & TEXTILES in Eastern Europe* 2018; 26, 6(132): 133-141. DOI: 10.5604/01.3001.0012.5167
4. Trotman E R. *Dyeing and Chemical Technology of Textile Fibres*, Fourth Edition, January 1970.
5. Behera B K, Pattanayak A K. *Indian J Fibre Text Res*, (33) (2008) 230.
6. Kawabata S. The Standardization and Analysis of Hand Evaluation, Japan, Osaka: Hand Eval. Standardization Committee, *Textile Mach. Soc. Jpn.*, 1980.
7. Study of the Characteristics of Polymer Deposition By Electrospraying, Amit Arunchandra Jadhav, School of Fashion and Textiles Design and Social Context Portfolio RMIT University January 2014, Doctor of Philosophy.
8. Nawaza N, Troynikovb O, Watson C. Evaluation of Surface Characteristics of Fabrics Suitable for Skin Layer of Firefighters' Protective Clothing. *International conference on Physics Science and Technology 2011*, Physics Procedia 22 (2011) 478 – 486.