

References

1. Oliveira J, Brichi GS, Marconcini JM, Mattoso LHC, Glenn GM, Medeiros ES. Effect of Solvent on the Physical and Morphological Properties of Poly(Lactic Acid) Nanofibers Obtained by Solution Blow Spinning. *Journal of Engineered Fibers and Fabrics* 2014; 9: 117-125.
2. Hekmati AH, Khenoussi N, Nouali H, Patarin J, Drean J-Y. Effect of Nanofiber Diameter on Water Absorption Properties and Pore Size of Polyamide-6 Electrospun Nanoweb. *Textile Research Journal* 2014; 84: 2045-2055.
3. Pillay V, Dott C, Choonara YE, Tyagi C, Tomar L, Kumar P, du Toit LC, Ndesendo VM, A Review of the Effect of Processing Variables on the Fabrication of Electrospun Nanofibers for Drug Delivery Applications. *Journal of Nanomaterials*, 2013.
4. Panthi G, Barakat NA, Risal P, Yousef A, Pant B, Unnithan AR, Kim HY. Preparation and Characterization of Nylon-6/Gelatin Composite Nanofibers via Electrospinning for Biomedical Applications. *Fibers and Polymers* 2013; 14: 718-723.
5. Kausar A. A Study on High-Performance Poly (Azo-Pyridine-Benzophenone-Imide) Nanocomposites Via Self-Reinforcement of Electrospun Nanofibers. *Iranian Polymer Journal* 2014; 23: 127-136.
6. Casasola R, Thomas NL, Trybala A, Georgiadou S. Electrospun Poly Lactic Acid (PLA) Fibres: Effect of Different Solvent Systems on Fibre Morphology and Diameter. *Polymer*, 2014, 55: 4728-4737.
7. Ahmet Ç, Kumbasar E P A, Akduman Ç. Çözgen Karışımının Elektrolif Çekim Yöntemi İle Üretilmiş Termoplastik Poliüretan Nanofibrerin Morfolojisine Etkisi, Tekstil Ve Konfeksiyon, 25 38-46.
8. Erdem R, Usta I, Akalin M, Atak O, Yuksek M, Pars A. The Impact Of Solvent Type And Mixing Ratios Of Solvents On The Properties Of Polyurethane Based Electrospun Nanofibers. *Applied Surface Science* 2015; 334: 227-230.
9. Choktaweesap N, Arayanarakul K, Aht-Ong D, Meechaisue C, Supaphol P. Electrospun Gelatin Fibers: Effect of Solvent System on Morphology and Fiber Diameters. *Polymer Journal* 2007; 39: 622-631.
10. Tungprapa S, Puangparn T, Weerasombut M, Jangchud I, Fakum P, Semongkhon S, Meechaisue C, Supaphol P. Electrospun Cellulose Acetate Fibers: Effect of Solvent System on Morphology and Fiber Diameter. *Cellulose* 2007; 14: 563-575.
11. Kaya A, Hockenberger A. Effects of Polymer Structure on the Electrospun Polyamide Nanofibers. *Journal of Textile & Apparel/Tekstil ve Konfeksiyon* 2017; 27.
12. Nirmala R, Jeong JW, Oh HJ, Navamathavan R, El-Newehy M, Al-Deyab SS, Kim HY. Electrical Properties of Ultrafine Nylon-6 Nanofibers Prepared Via Electrospinning. *Fibers and Polymers* 2011; 12: 1021-1024.
13. Pant HR, Bajgai MP, Nam KT, Seo YA, Pandeya DR, Hong ST, Kim HY. Electrospun Nylon-6 Spider-Net Like Nanofiber Mat Containing TiO_2 Nanoparticles: A Multifunctional Nanocomposite Textile Material. *Journal of Hazardous Materials* 2011; 185: 124-130.
14. Nirmala R, Panth HR, Yi C, Nam KT, Park S-J, Kim HY, Navamathavan R. Effect of Solvents on High Aspect Ratio Polyamide-6 Nanofibers Via Electrospinning. *Macromolecular Research* 2010; 18: 759-765.

15. Hasan MM, Nayem KA, Hossain MB, Nahar S. Production of Tissue Engineering Scaffolds from Poly Caprolactone (PCL) and its Microscopic Analysis. *International Journal of Textile Science*, 2014; 3: 39-43.
16. Arayanarakul K, Choktaweesap N, Aht-ong D, Meechaisue C, Supaphol P. Effects of Poly (Ethylene Glycol), Inorganic Salt, Sodium Dodecyl Sulfate, and Solvent System on Electrospinning of Poly (Ethylene Oxide). *Macromolecular Materials and Engineering*, 2006; 29: 581-591.
17. Härdelin L, Thunberg J, Perzon E, Westman G, Walkenström P, Gatenholm P, Electrospinning of Cellulose Nanofibers from Ionic Liquids: The Effect of Different Cosolvents. *Journal of Applied Polymer Science* 2012; 125: 1901-1909.
18. Liu H, Tang C. Electrospinning of Cellulose Acetate in Solvent Mixture N, N-Dimethylacetamide (Dmac)/Acetone. *Polymer Journal* 2007; 39: 65.
19. Xu S, Zhang J, He A, Li J, Zhang H, Han CC. Electrospinning of Native Cellulose from Nonvolatile Solvent System. *Polymer* 2008; 49: 2911-2917.
20. Son WK, Youk JH, Lee TS, Park WH. Electrospinning of Ultrafine Cellulose Acetate Fibers: Studies of a New Solvent System and Deacetylation of Ultrafine Cellulose Acetate Fibers. *Journal of Polymer Science Part B: Polymer Physics*, 2004; 42: 5-11.
21. Wu X, Wang L, Yu H, Huang Y. Effect of Solvent on Morphology of Electrospinning Ethyl Cellulose Fibers. *Journal of Applied Polymer Science* 2005; 97: 1292-1297.
22. Son WK, Youk JH, Lee TS, Park WH. The Effects of Solution Properties and Polyelectrolyte on Electrospinning of Ultrafine Poly (Ethylene Oxide) Fibers. *Polymer* 2004; 45: 2959-2966.
23. Düzyer Ş. Fabrication of Electrospun Poly (Ethylene Terephthalate) Scaffolds: Characterization and their Potential on Cell Proliferation in Vitro. *Journal of Textile & Apparel/Tekstil ve Konfeksiyon* 2017; 27.
24. Yanilmaz M, Dirican M, Zhang X. Evaluation of electrospun SiO₂/nylon 6, 6 nanofiber membranes as a thermally-stable separator for lithium-ion batteries. *Electrochimica Acta*, 2014; 133: 501-508.
25. Ryu YJ, Kim HY, Lee KH, Park HC, Lee DR. Transport Properties of Electrospun Nylon 6 Nonwoven Mats. *European Polymer Journal* 2003; 39: 1883-1889.
26. Maleki H, Gharehaghaji A, Moroni L, Dijkstra PJ. Influence of the Solvent Type on the Morphology and Mechanical Properties of Electrospun PLLA Yarns. *Biofabrication*, 2013; 5: 035014.
27. Baji A, Mai Y-W, Wong S-C. Effect of Fiber Diameter on the Deformation Behavior of Self-Assembled Carbon. Nanotube Reinforced Electrospun Polyamide 6, 6 Fibers. *Materials Science and Engineering: A* 2011; 528: 6565-6572.