

References

1. Lewandowski S. Monitorowanie produkcji i jej jakości jednym z celów procesu przędzenia. *Przegląd Włókienniczy – WOS* 2007; 2: 58-60.
2. Jackowska-Strumiłło L, Cyniak D, Czekalski J, Jackowski T. Neural Model of the Spinning Process Dedicated to Predicting Properties of Cotton-Polyester Blended Yarns on the Basis of the Characteristics of Feeding Streams. *FIBRES & TEXTILES in Eastern Europe* 2008; 16, 1(66): 28-36.
3. Bilińska L, Żyła R, Smółka K, Gmurek M, Ledakowicz S. Modeling of Ozonation of C.I. Reactive Black 5 Through a Kinetic Approach. *FIBRES & TEXTILES in Eastern Europe* 2017; 25, 5(125): 54-60. DOI: 10.5604/01.3001.0010.4628.
4. Petruyte S. Influence of Technological Parameters on the Periodical Effects of Fancy Yarns. *FIBRES & TEXTILES in Eastern Europe* 2008; 16, 3(68): 25-29.
5. Hasani H, Tabatabaei SA. Optimizing Spinning Variables to Reduce the Hairiness of Rotor Yarns Produced from Waste Fibers Collected from the Ginning Process. *FIBRES & TEXTILES in Eastern Europe* 2011, 19, 3(86): 21-25.
6. Mikołajczyk Z. Optimisation of the Knitting Process on Warp-Knitting Machines in the Aspect of the Properties of Modified Threads and the Vibration Frequency of the Feeding System. *FIBRES & TEXTILES in Eastern Europe* 2011, 19, 6(89): 75-79.
7. Eldeeb M, Demir A. Optimising the Production Process of Rieter Air Jet Spun Yarns and a Model for Prediction of their Strength. *FIBRES & TEXTILES in Eastern Europe* 2018; 26, 1(127): 36-41. DOI: 10.5604/01.3001.0010.7794.
8. Urbańczyk G. Nauka o włóknie cz.II, Lodz University of Technology Press, 1978 (in polish).
9. Karbownik I, Rac O, Fiedot M, Suchorska-Woźniak P, Teterycz H. In Situ Preparation of Silver–Polyacrylonitrile Nanocomposite Fibres. *European Polymer Journal* 2015; 69: 385–395.
10. Karbownik I, Rac-Rumijowska O, Fiedot-Toboła M, Rybicki T, Teterycz H. The Preparation and Characterization of Polyacrylonitrile-Polyaniline (PAN/PANI). *Fibers Materials* 2019; 12, 664.
11. Rac O, Karbownik I, Fiedot M, Rybicki T, Karpińska A. Composite Fibres Doped with Carbon Nanoparticles for use in Textronics. *IMAPS, 2016; 25-28 September, Wałbrzych*.
12. Kozicki M, Sasiadek E, Karbownik I, Maniukiewicz W. Doped Polyacrylonitrile

- Fibres as UV Radiation Sensors. *Sens. and Actuators B* 2015; 213, 234-243.
13. Mikołajczyk T, Boguń M, Szparaga G. Influence of the Type of Montmorillonite and the Conditions of Fibre Formation from a Polyacrylonitrile Nanocomposite on the Fibre Properties. *FIBRES & TEXTILES in Eastern Europe* 2007; 15, 3(62): 25-31.
 14. Rahatekar SS, Rasheed A, Jain R, Zammarano M, Koziol KK, et al, Solution Spinning of Cellulose Carbon Nanotube Composites using Room Temperature Ionic Liquids. *Polym.* 2009; 50: 457-458.
 15. Karbownik I, Rybicki T, Karpińska A, Teterycz H. PAN Fibers with Nanoprecipitated Ag and Au for Use in Textronics. *Mater. Sci.-Pol.* 2016; 34: 564-570.
 16. Karbownik I, Teterycz H, Rybicki T, Kulpiński P, et all. Sposób wytwarzania włókien poliakrylonitrylowych o właściwościach antybakteryjnych, antygrzybiczych lub/i elektroprzewodzących. Patent PL 229181.
 17. Karbownik I, Fiedot M, Rac O, Rybicki T, Suchorska-Woźniak P, Teterycz H. Effect of Doping Polyacrylonitrile Fibers on their Structural and Mechanical Properties. *Polym.* 2015; 75: 97-108.
 18. Karbownik I. Modyfikacja włókien z zastosowaniem wybranych technik i nanotechnologii, Lodz University of Technology Monographs, 2016 (in polish)
 19. Mikołajczyk T, Boguń M, Kurzak A, Wójcik M, Nowicka K. Influence of Forming Conditions on the Tensile Strength Properties of PAN Fibres Containing a Ferromagnetic Nanoaddition. *FIBRES & TEXTILES in Eastern Europe* 2007, 15, 3(62): 19-24.
 20. Broda J, Przybyło S, Lewandowski S. Selection of Optimal Formation Parameters of Polyporpylene Fibrillated Fibres Designed for Concrete Reinforcement. *FIBRES & TEXTILES in Eastern Europe* 2012; 20, 6A(95): 69-74.
 21. Mikołajczyk T, Szparaga G, Rabiej S, Frączek-Szczypta A. Influence of Formation Conditions on the Structure and Properties of Nanocomposite PAN Fibres Containing Silver and Hydroxyapatite Nanoadditives. *FIBRES & TEXTILES in Eastern Europe* 2010; 18, 5(82): 16-23.
 22. Boguń M, Mikołajczyk T. Influence of Coagulation Bath Temperature on the Porous Structure and Strength Properties of PAN Fibres Including Montmorillonite. *FIBRES & TEXTILES in Eastern Europe* 2006; 14, 3(57): 19-22.
 23. Mikołajczyk T, Szparaga G, Rabiej S, Frączek-Szczypta A. Influence of Formation Conditions on the Structure and Properties of Nanocomposite PAN Fibres Containing Silver and Hydroxyapatite Nanoadditives. *FIBRES & TEXTILES in Eastern Europe*

2010, 18, 5(82): 16-23.

24. Boguń M, Mikołajczyk T. Influence of Coagulation Bath Temperature on the Porous Structure and Strength Properties of PAN Fibres Including Montmorillonite. *FIBRES & TEXTILES in Eastern Europe* 2006; 14, 3(57): 19-22.
25. Mikołajczyk T, Szparaga G. Influence of Fibre Formation Conditions on the Properties of Nanocomposite PAN Fibres Containing Nanosilver. *FIBRES & TEXTILES in Eastern Europe* 2009; 17, 4(75): 30-36.
26. Mikołajczyk T, Olejnik M. Influence of the Plastification Drawing Conditions and Distribution of Drawing Ratios on the Structure and Properties of Fibres Made of a Polyimidoamide Nanocomposite Containing Montmorillonite. *FIBRES & TEXTILES in Eastern Europe* 2009; 17, 1(72): 20-25.
27. ATmega162(V)-Complete Datasheet – 8-bit AVR Microcontroller with 16K Bytes In-System Programmable Flash, ATmega162, ATmega162V (pdf document).
28. The RS-485 Design Guide – Texas Instruments Application Report, 2008, revised 2016, (slla272c.pdf, pdf document).
29. PN-EN ISO 2062:2010 Textiles-Yarns from packages – Determination of single-end breaking force and elongation at break using constant rate of extension (CRE) tester.