

## References

1. Worford P. Press Section Water Balance Testing. *Tappi Journal* 2002; 1(7): 3-7.
2. Kääpä O, Karvinen J. Influence of Vacuum Capacity on Press Dewatering and Energy Consumption. *Wochenblatt für Papierfabrikation* 2004; 132(11-12): 636-639.
3. Gabriele E. Felt Suction Boxes - New Dewatering Guidelines For Modern Press Felts. *Wochenblatt für Papierfabrikation* 2000; 133(21): 1327-1330.
4. Reczulski M. Uhle boxes– a way to condition press felts (in Polish). *Przegląd Papierniczy* 2018; 74(12): 791-794.
5. Paulaporo H. *Papermaking Science and Technology. Book 8. Papermaking Part #1. Stock Preparation and Wet End*. Helsinki, 2000.
6. Raubic L. A New Look into the Uhle Dewatering Process. *Appita Journal* 2014; 67(2): 106-108.
7. Kawka W.; Principles of the Through-Air Dewatering Theory for Selected Fibrous Materials (Press Section Felts). *FIBRES & TEXTILES in Eastern Europe* 2009; 17, 3(74): 95-97.
8. Azeem M, Ahmad Z, Wiener J, Fraz A, Siddique HF, Havalka A. Influence of Weave Design and Yarn Types on Mechanical and Surface Properties of Woven Fabric. *FIBRES & TEXTILES in Eastern Europe* 2018; 26, 1(127): 42-45. DOI: 10.5604/01.3001.0010.7795.
9. Jankoska M, Demboski G. Influence of Structure Variation and Finishing on Woven Fabric Thermal Properties. *FIBRES & TEXTILES in Eastern Europe* 2018; 26, 1(127): 120-124. DOI: 10.5604/01.3001.0010.7807.
10. Milašius R, Legaudienė B, Laureckienė G. Influence of Weave Parameters on Woven Fabric Tear Strength. *FIBRES & TEXTILES in Eastern Europe* 2018; 26, 4(130): 48-51. DOI: 10.5604/01.3001.0012.1312.