

References

1. Seager R, Zhang S, Chauraya A, et al. Effect of the Fabrication Parameters on the Performance of Embroidered Antennas. *IET Microwaves Antennas & Propagation* 2013; 7(14): 1174–1181
2. Marindra A, Pongpaibool P, Wallada W, et al. An Optimized Ink-reducing Hollowed-out Arm Meander Dipole Antenna Structure for Printed RFID Tags. *International Journal of Microwave and Wireless Technologies* 2017; 9(2):469-479.
3. Ginestet G, Brechet N, Torres J, et al. Embroidered Antenna-Microchip Interconnections and Contour Antennas in Passive UHF RFID Textile Tags. *IEEE Antennas and Wireless Propagation Letters* 2017; 16: 1205-1208.
4. Aris T, Whittow W. Embroidery and related Manufacturing Techniques for Wearable Antennas: Challenges and Opportunities. *Electronics* 2014; 3(2): 314-338.
5. Xu S, Zhang Y, Hu J, et al. Effect of Process Parameters on S-Parameter of Fabric-Based Embroidered Transmission Line. *Journal of Donghua University* 2017; 34(6):736-740.
6. Ignacio G, Raul F, Jose A T, Embroidery Manufacturing Techniques for Textile Dipole Antenna Applied to Wireless Body Area Network. *Text Res J.* 2019; 89(8): 1573-1581.
7. Moradi E, Bjominen T, Ukkonen, et al. Effects of Sewing Pattern on the Performance of Embroidered Dipole-Type RFID Tag Antennas. *IEEE Antennas and Wireless Propagation Letters* 2012; 11:1482-1485.
8. Dias T, Zhang S, Acti T, et al. Effect of the Fabrication Parameters on the Performance of Embroidered Antennas. *IET Microwaves, Antennas & Propagation* 2013; 7(14):1174-1181.
9. Koski K, Sydänheimo L and Rahmat-Samii Y. Fundamental Characteristics of Electro-Textiles in Wearable UHF RFID Patch Antennas for Body-centric Sensing Systems. *IEEE T Antenn Propag.* 2014; 62(12): 6454-6462.
10. Zhang W, Gan Q. *Design, Simulation and Practice of UHF RFID Tag Antenna*. Electronic Industry Press, 2012; p.36-45.
11. Toh BY, Cahill R, Fusco VF. Understanding and Measuring Circular Polarization. *IEEE T Educ.* 2003; 46(3): 313-318.