

12. Akcakoca EP, Ozguney AT, Atav R. The efficiency of washing agents in the post-dyeing removal of hydrolyzed reactive dye. *Dyes and Pigments* 2007; 72: 23-27.
13. Shaikh IA, Ahmad N, Urooj F. A novel method to improve color fastness of deep shade reactive dyeing using ozone in washing off. *AATCC Review* 2010; 10: 73-77.
14. Akalin M, Merdan N, Kocak D. Effects of ultrasonic energy on the wash fastness of reactive dyes. *Ultrasonics* 2004; 42:161-164.
15. Suwanruji P, Freeman HS. Design, synthesis and application of easy wash-off reactive dyes. *Coloration Technology* 2006; 122: 27-36.
16. Verma AK, Dash RR, Bhunia P. A review on chemical coagulation/flocculation technologies for removal of colour from textile wastewaters. *Journal of Environmental Management* 2012; 93: 154-168.
17. Anjaneyulu Y, Chary NS, Raj DSS. Decolourization of industrial effluents available methods and emerging technologies-A Review. *Reviews in Environmental Science and Biotechnology* 2005; 4: 245-273.
18. Golob V, Vinder A, Simonic M. Efficiency of coagulation/flocculation method for treatment of dye bath effluents. *Dyes and Pigments* 2005; 67: 93-97.
19. Papic S, Koprivanac N, Bozic AL. Removal of reactive dyes from wastewater using Fe(III) coagulant. *Coloration Technology* 2000; 161: 352-358.
20. Kim TH, Park C, Shin EB, Kim S. Decolourization of disperse and reactive dyes by continuous electrocoagulation process. *Desalination* 2002; 150: 165-175.
21. Georgiou D, Aivazidis A, Hatiras J, Gimouhopoulos K. Treatment of cotton textile wastewater using lime and ferrous sulfate. *Water Research* 2003; 37: 2248-2250.
22. Errais E, Duplay J, Darragi F. Textile dye removal by natural clay – Case study of Fouchana Tunisian clay. *Environmental Technology* 2010; 31: 373-38.
23. Wong PW, Teng TT, Rahman NA, Norulaini N. Efficiency of the Coagulation-Flocculation method for the treatment of dye mixtures containing disperse and reactive dye. *Water Quality Research Journal of Canada* 2007; 42:13-20.
24. Duan J, Gregory J. Coagulation by hydrolyzing metal salts. *Advances in Colloid and Interface Science* 2003; 100: 475-502.
25. Tan BJ, Teng TT, Omar AK. Removal of dyes and industrial dye wastes by magnesium chloride. *Water Research* 2000; 34: 597-601.
26. Ooi PY, Teng TT, Omar AKM, Norulaini NAR. Removal of dyes by aqueous mixed coagulants. *ASEAN Journal of Chemical Engineering* 2005; 5: 52-64.

Zr. Canizares P, Jimenez C, Martinez F,



INSTITUTE OF BIOPOLYMERS AND CHEMICAL FIBRES

LABORATORY OF BIODEGRADATION

The Laboratory of Biodegradation operates within the structure of the Institute of Biopolymers and Chemical Fibres. It is a modern laboratory with a certificate of accreditation according to Standard PN-EN/ISO/IEC-17025: 2005 (a quality system) bestowed by the Polish Accreditation Centre (PCA). The laboratory works at a global level and can cooperate with many institutions that produce, process and investigate polymeric materials. Thanks to its modern equipment, the Laboratory of Biodegradation can maintain cooperation with Polish and foreign research centers as well as manufacturers and be helpful in assessing the biodegradability of polymeric materials and textiles.

The Laboratory of Biodegradation assesses the susceptibility of polymeric and textile materials to biological degradation caused by microorganisms occurring in the natural environment (soil, compost and water medium). The testing of biodegradation is carried out by oxygen using innovative methods like respirometric testing with the continuous reading of the CO₂ delivered. The laboratory's modern MICRO-OXYMAX RESPIROMETER is used for carrying out tests in accordance with International Standards.



The methodology of biodegradability testing has been prepared on the basis of the following standards:

- **testing in aqueous medium:** 'Determination of the ultimate aerobic biodegradability of plastic materials and textiles in an aqueous medium. A method of analysing the carbon dioxide evolved' (PN-EN ISO 14 852: 2007 and PN-EN ISO 8192: 2007)
- **testing in compost medium:** 'Determination of the degree of disintegration of plastic materials and textiles under simulated composting conditions in a laboratory-scale test. A method of determining the weight loss' (PN-EN ISO 20 200: 2007, PN-EN ISO 14 045: 2005, and PN-EN ISO 14 806: 2010)
- **testing in soil medium:** 'Determination of the degree of disintegration of plastic materials and textiles under simulated soil conditions in a laboratory-scale test. A method of determining the weight loss' (PN-EN ISO 11 266: 1997, PN-EN ISO 11 721-1: 2002, and PN-EN ISO 11 721-2: 2002).

ment of wastewaters. *Journal of Haz*



AB 388



The following methods are applied in the assessment of biodegradation: gel chromatography (GPC), infrared spectroscopy (IR), thermogravimetric analysis (TGA) and scanning electron microscopy (SEM).

Contact:

INSTITUTE OF BIOPOLYMERS AND CHEMICAL FIBRES
ul. M. Skłodowskiej-Curie 19/27, 90-570 Łódź, Poland
Agnieszka Gutowska Ph. D.,
tel. (+48 42) 638 03 31, e-mail: lab@ibwch.lodz.pl