

Periodic and Chaotic Motion in Sirofil Yarn Spinning

Modern Textile Institute,
Donghua University,
Shanghai, China
E-mail: ihhe@dhu.edu.cn
ijnsns@yahoo.com.cn

Abstract

A dynamic model is established for two-strand yarn processing. The oscillating frequencies of Sirofil spinning in vertical and horizontal directions are approximately obtained. The stability and chaotic characters of Sirofil spinning are analysed analytically, and an optimal condition for the spinning system is suggested.

Key words: two-strand spinning, Sirospun, Sirofil, chaotic motion.

vortex spinning [1, 2]. More importantly, Sirofil yarns have a low initial modulus, and hence the yarns are softer than normal ring spun yarns [3]. Furthermore, the strands are texturised to improve the bulk of the resultant yarns, which have been demonstrated to possess more desirable properties, for example the weavability of fabric formed with Sirofil yarns (See Figure 1) is significantly better than its counterparts.

In our previous study [4 - 7], the linear and nonlinear dynamical characters of Sirospun were studied using the homotopy perturbation method [8, 9] or the variational method [8, 10]. In this paper, we will develop a dynamical model for Sirofil spinning. The characteristics of two-strand spun yarns mainly depends on how the two strands are combined and mixed. The different oscillating frequencies of the convergent point in both vertical and horizontal directions have been proven to be the dominant factors [6].

Here M is the total mass of a fixed control volume $ABCD$ illustrated in Figure 3; the control volume is chosen in such a way that the mass centre coincides with the convergent point (O) of the two strands.

If x and y are much smaller than $\sqrt{L_1^2 + H^2}$ and $\sqrt{L_2^2 + H^2}$, and we then apply the binomial theorem to expand the square-root terms, we have approximately (equation 1.a)




Figure 2. The dynamical illustration of two-strand spun??

Introduction

Sirofil has been widely used to produce composite yams with a low twist factor in a single operation during yarn spinning. Sirofil yarns are stronger and have larger extensibility and rupture energy than corresponding normal ring spun yarns or air-




Figure 1. Two-Strand Yarn Spinning (Sirofil Spinning).

Dynamical model

Figure 1 illustrates two-strand yarn spinning. We first assume the system is in a stable condition. Using our quasistatic model [4], the convergent point can be determined with ease. Due to some perturbations, the convergent point (equilibrium position, O in Figure 2) moves to an instantaneous new position (O'). The distances x and y are measured from the equilibrium position.

Let the ends of the two strands above the convergent point be fixed at a distance $L_1 + L_2$ apart, and the equilibrium position be H below. The equations of the motion in x - and y -directions are

$$\begin{cases} M \frac{d^2 x}{dt^2} + F_1 \cos \alpha - F_2 \cos \beta = 0 \\ M \frac{d^2 y}{dt^2} + F_1 \sin \alpha + F_2 \sin \beta - F = 0 \end{cases} \quad (1)$$






Figure 3. The control volume, the mass centre at the convergent point.



Equation (1) becomes

$$\begin{cases} \ddot{x} + \omega_1^2 x + by = 0 \\ \ddot{y} + \omega_2^2 y + bx = 0 \end{cases} \quad (2)$$

where

$$\begin{aligned} \omega_1^2 &= \frac{F_1 \cos^3 \alpha_1 + F_2 \cos^3 \alpha_2}{MH} \\ b &= \frac{F_2 \sin \alpha_2 \cos^2 \alpha_2 - F_1 \sin \alpha_1 \cos^2 \alpha_1}{MH} \\ \omega_2^2 &= \frac{F_1 \sin^2 \alpha_1 \cos \alpha_1 + F_2 \sin^2 \alpha_2 \cos \alpha_2}{MH} \end{aligned}$$

In the case of $b = 0$, i.e., $\alpha_1 = \alpha_2$ and $F_1 = F_2$, the system turns out to be Sirospun spinning, which was discussed in [5, 6].

Solving Equations (2), we can obtain the following solutions:

$$\begin{aligned} x &= a \sin p_1 t + b \sin p_2 t \\ y &= c \sin p_1 t + d \sin p_2 t \end{aligned} \quad (3)$$

where

$$\begin{aligned} p_1 &= \sqrt{\frac{\omega_1^2 + \omega_2^2 + \sqrt{(\omega_1^2 - \omega_2^2)^2 + 4b^2}}{2}} \\ p_2 &= \sqrt{\frac{\omega_1^2 + \omega_2^2 - \sqrt{(\omega_1^2 - \omega_2^2)^2 + 4b^2}}{2}} \end{aligned} \quad (4)$$

a , b , c , and d are constants which can be determined by the initial conditions. The trajectories of the convergent point are illustrated in Figure 4.

From Figure 4 we know that we have closed trajectories when p_1/p_2 is an integer or can lead to a ratio of two integer numbers, i.e., $p_1/p_2 = n/m$, where m and n are integer numbers. Closed trajectory means that the convergent point, O , moves periodically.

Chaotic motion occurs when ω_1/ω_2 or p_1/p_2 are not rational numbers as illustrated in Figure 5.

$$\begin{cases} \cos \alpha = \frac{L_1 + x}{\sqrt{(L_1 + x)^2 + (H + y)^2}} = \cos \alpha_1 - \frac{\sin \alpha_1 \cos^2 \alpha_1}{H} x + \frac{\sin^2 \alpha_1 \cos \alpha_1}{H} y \\ \cos \beta = \frac{L_2 - x}{\sqrt{(L_2 - x)^2 + (H + y)^2}} = \sin \alpha_1 + \frac{\cos^3 \alpha_1}{H} x - \frac{\sin \alpha_1 \cos^2 \alpha_1}{H} y \end{cases} \quad 1.a$$

and

$$\begin{cases} \sin \alpha = \frac{H + y}{\sqrt{(L_1 + x)^2 + (H + y)^2}} = \sin \alpha_2 - \frac{x}{H} \cos^3 \alpha_2 - \frac{y}{H} \sin \alpha_2 \cos^2 \alpha_2 \\ \sin \beta = \frac{H + y}{\sqrt{(L_2 - x)^2 + (H + y)^2}} = \cos \alpha_2 + \frac{\sin \alpha_2 \cos^2 \alpha_2}{H} x + \frac{\sin^2 \alpha_2 \cos \alpha_2}{H} y \end{cases}$$

Conclusion

To conclude, we obtained conditions for stability ($b=0$ for Sirospun spinning), periodic and chaotic motion in the two-strand spun process. The results show that by suitably choosing certain geometry parameters and forces, the spinning process can be optimally matched. Chaotic motion should be avoided in practical applications as chaotic motion leads to yarns easily breaking.

Acknowledgment

The project is/was supported by the National Natural Science Foundation of China under grant No. 10572038 and the Program for New Century Excellent Talents in University.

References

- Liu Y, Xu L. Controlling air vortex in air-vortex spinning by Zeng-He model, *International Journal of Nonlinear Sciences and Numerical Simulation*, 7 (4) (2006): 389-392.
- Zeng YC, Yu CW. A flexible fiber model for dynamic simulation of fibers in high speed air flows, *International Journal of Nonlinear Sciences and Numerical Simulation*, 7 (4)(2006): 427-430.
- Wang XG, Wang LJ and Liu X. The Quality and Processing Performance of Alpaca

- Fibres, RIRDC Publication No 03/128, RIRDC Project No UD-2A, November 2003.
- He JH, Yu YP, Pan N, et al., Quasistatic model for two-strand yarn spinning, *Mechanics Research Communications* 32 (2)(2005)197-200.
- He JH, Yu YP, Yu JY, et al., A linear dynamic model for two-strand yarn spinning, *Textile Research Journal* 75 (1)(2005) 87-90.
- He JH, Yu YP, Yu JY, et al., A nonlinear dynamic model for two-strand yarn spinning, *Textile Research Journal* 75 (2) (2005) 181-184.
- He JH. Variational Approach to Nonlinear Coupled Oscillators Arising in Sirospun Yarn Spinning, *Fibres & Textiles in Eastern Europe*, 15(1)(2007):31-34.
- He JH. Some Asymptotic Methods for Strongly Nonlinear Equations, *International Journal of Modern Physics B*, 20(10) (2006) 1141-1199
- Ganji DD, Sadighi A. Application of He's homotopy-perturbation method to nonlinear coupled systems of reaction-diffusion equations, *International Journal of Nonlinear Sciences and Numerical Simulation*, 7 (4)(2006): 411-418
- Odibat ZM, Momani S. Application of variational iteration method to Nonlinear differential equations of fractional order, *International Journal of Nonlinear Sciences and Numerical Simulation*, 7 (1) (2006): 27-34

Received 04.08.2006 Received 23.04.2007



FIBRES & TEXTILES in Eastern Europe

reaches all corners of the world! It pays to advertise your products and services in our magazine! We'll gladly assist you in placing your ads.