

coating for polyester and cotton fabric. *Fire Mat* 2002; 26: 149-154.

6. Skoc MS, Macan J, Pezelj E. Modification of polyurethane-coated fabrics by sol-gel thin films. *Appl. Polym. Sci.* 2013. DOI: 10.1002/APP.39914.
7. Alongi J, Carosio F, Malucelli G. Influence of ammonium polyphosphate-/poly(acrylic acid)-based layer by layer architectures on the char formation in cotton, polyester and their blends. *Polym. Degrad. Stab.* 2012; 97: 1644-1653.
8. Drevelle C, Duquesne S, Le Bras M, Lefebvre J, Delobel R, Castrovinci A, Magniez C, Vouters M. Influence of ammonium polyphosphate on the mechanism of thermal degradation of an acrylic binder resin. *J. Appl. Polym. Sci.* 2004; 94: 717-729.
9. Carosio F, Alongi J, Malucelli G. Layer by layer ammonium polyphosphate-based coatings for flame retardancy of polyester-cotton blends. *Carbohydrate Polymers* 2012; 88: 1460-1469.
10. Carosio F, Alongi J, Malucelli G. Flammability and combustion properties of ammonium polyphosphate-/poly(acrylic acid)-based layer by layer architectures deposited on cotton, polyester and their blends. *Polym. Degrad. Stab.* 2013; 98: 1626-1637.
11. Drevelle C, Lefebvre J, Duquesne S, Le Bras M, Poutch F, Vouters M, Magniez C. Thermal and fire behavior of ammonium polyphosphate/acrylic coated cotton/PSFR fabric. *Poly. Degrad. Stab.* 2005; 88: 130-137.
12. Lecomte HA, Liggat JJ. Commercial fire-retarded PET formulations-relationship between thermal degradation behavior and fire-retardant action. *Polym. Degrad. Stab.* 2008; 93: 498-506.
13. Mathews MC. Durable and non-toxic topical flame retardants for cotton and cotton blends. In: *Textile Engineering*. Raleigh, North Carolina, 2007.
14. Schartel B. Phosphorus-based flame retardancy mechanisms – old hat or a starting point for future development. *Materials* 2010; 3: 4710-4745.
15. Zhang H. Textile flame retardant review. *Mod. Appl. Sci.* 2009; 3: 129-133.
16. Bisschoff J. Phosphorous flame retardants. In: *Oxygenated hydrocarbon compounds as flame retardants for polyester fabric*. University of Pretoria, 2000. p. 38-45.



## INSTITUTE OF BIOPOLYMERS AND CHEMICAL FIBRES

### LABORATORY OF BIODEGRADATION

The Laboratory of Biodegradation operates within the structure of the Institute of Biopolymers and Chemical Fibres. It is a modern laboratory with a certificate of accreditation according to Standard PN-EN/ISO/IEC-17025: 2005 (a quality system) bestowed by the Polish Accreditation Centre (PCA). The laboratory works at a global level and can cooperate with many institutions that produce, process and investigate polymeric materials. Thanks to its modern equipment, the Laboratory of Biodegradation can maintain cooperation with Polish and foreign research centers as well as manufacturers and be helpful in assessing the biodegradability of polymeric materials and textiles.

The Laboratory of Biodegradation assesses the susceptibility of polymeric and textile materials to biological degradation caused by microorganisms occurring in the natural environment (soil, compost and water medium). The testing of biodegradation is carried out in oxygen using innovative methods like respirometric testing with the continuous reading of the CO<sub>2</sub> delivered. The laboratory's modern MICRO-OXYMAX RESPIROMETER is used for carrying out tests in accordance with International Standards.



The methodology of biodegradability testing has been prepared on the basis of the following standards:

- **testing in aqueous medium:** 'Determination of the ultimate aerobic biodegradability of plastic materials and textiles in an aqueous medium. A method of analysing the carbon dioxide evolved' (PN-EN ISO 14 852: 2007, and PN-EN ISO 8192: 2007)
- **testing in compost medium:** 'Determination of the degree of disintegration of plastic materials and textiles under simulated composting conditions in a laboratory-scale test. A method of determining the weight loss' (PN-EN ISO 20 200: 2007, PN-EN ISO 14 045: 2005, and PN-EN ISO 14 806: 2010)
- **testing in soil medium:** 'Determination of the degree of disintegration of plastic materials and textiles under simulated soil conditions in a laboratory-scale test. A method of determining the weight loss' (PN-EN ISO 11 266: 1997, PN-EN ISO 11 721-1: 2002, and PN-EN ISO 11 721-2: 2002).



AB 388



The following methods are applied in the assessment of biodegradation: gel chromatography (GPC), infrared spectroscopy (IR), thermogravimetric analysis (TGA) and scanning electron microscopy (SEM).

#### Contact:

INSTITUTE OF BIOPOLYMERS AND CHEMICAL FIBRES  
ul. M. Skłodowskiej-Curie 19/27, 90-570 Łódź, Poland  
Agnieszka Gutowska Ph. D.,  
tel. (+48 42) 638 03 31, e-mail: lab@ibwch.lodz.pl