

## References

1. Wang XC, Liu Z, Zhou Z. Virtual metal model for fast computation of shielding effectiveness of blended electromagnetic interference shielding fabric. *Int. J. Appl. Electrom.* 2014; 44(1): 87-97.
2. Knittel D, Schollmeyer E. Electrically high-conductive textiles. *Synthetic Met.* 2009; 159(14): 1433-1437.
3. Liu Z, Wang XC. Relation between shielding effectiveness and tightness of electromagnetic shielding fabric. *J. Ind. Text.* 2013; 43(2): 302-316.
4. Hakansson E, Amie A, Kaynak A. Dielectric characterization of conducting textiles using free space transmission measurements: Accuracy and methods for improvement. *Synthetic. Met.* 2007; 157(24): 1054-1063.
5. Yildiz Z, Usta I, Gungor A. Investigation of the Electrical Properties and Electromagnetic Shielding Effectiveness of Polypyrrole Coated Cotton Yarns. *Fibres & Textiles in Eastern Europe* 2013; 21(2): 32-37.
6. Wang XC, Liu Z, Zhou Z. Automatic identification of gray porosity and its influence on shielding effectiveness for electromagnetic shielding fabric. *Int. J. Cloth. Sci. Tech.* 2014; 26(5): 424-436.
7. Liu Z, Wang XC. Influence of fabric weave type on the effectiveness of electromagnetic shielding woven fabric. *J. Electromagnet. Wave.* 2012; 26(14-15): 1848-1856.
8. Ortlek HG, Saracoglu OG, Saritas O, Bilgin S. Electromagnetic shielding characteristics of woven fabrics made of hybrid yarns containing metal wire. *Fibre Polym.* 2012; 13(1): 63-67.
9. Liu Z, Wang XC. Manufacture and performance evaluation of solar garment, *J. Clean Prod.* 2013; 42: 96-102.
10. Rybicki T, Brzezinski S, Lao M, et al. Modelling Protective Properties of Textile Shielding Grids Against Electromagnetic Radiation. *Fibres & Textiles in Eastern Europe* 2013; 21(1): 78-82.
11. Ching IS, Jin TC. Effect of stainless steel-containing fabrics on electromagnetic shielding effectiveness. *Textile Res. J.* 2004; 74(1): 51-54.
12. Wang XC, Liu Z. Influence of fabric density on shielding effectiveness of electromagnetic shielding fabric. *Przeglađ Elektrotechniczny* 2012; 88(11a): 236-238.
13. Wang XC, Li XJ. Recognition of fabric density with quadratic local extremum. *Int. J. Cloth. Sci. Tech.* 2012; 24(5): 328-338.
14. Brzezinski S, Rybicki T, Karbownik L, et al. Textile Multi-layer Systems for Protection against Electromagnetic Radiation. *Fibres & Textiles in Eastern Europe* 2009; 17(2): 66-71.
15. Wang XC, Liu Z, Zhou Z. Rapid computation model for accurate evaluation of electromagnetic interference shielding effectiveness of fabric with hole based on equivalent coefficient. *Int. J. Appl. Electrom.* 2015; 47(1): 177-185.
16. Qian ZM, Chen ZJ. *Electromagnetic compatibility design and interference suppression technology*. Ed. Zhejiang University Press, Hangzhou, 2000.
17. Yang YN, Zhang WY, Bai WF. The Microwave Absorbing Properties of Stainless Steel Fibres. *Rare Metals Letters* 2006; 25(8): 33-37.
18. Wang XC, Liu Z, Jiao ML. Computation model of shielding effectiveness of symmetric partial for anti-electromagnetic radiation garment. *Progress In Electromagnetics Research B* 2013; 47: 19-35. doi:10.2528/PIERB12111102.