

References

1. Amuda O S, Amoo I A. Coagulation/flocculation process and sludge conditioning in beverage industrial wastewater treatment. *Journal of Hazardous Materials* 2007; 141: 778-783.
2. Verma S, Prasad B, Mishra I., Pretreatment of petrochemical wastewater by coagulation and flocculation and the sludge characteristics. *Journal of Hazardous Materials*, 2010; 178, 1055-1064.
3. Allegre C, Maisseu M, Charbit F and Moulin P. Coagulation-flocculation-decantation of dye house effluents. *Journal of Hazardous Materials* 2004; B116, 57-64.
4. Chen Y, Wang W, Wei M, Chiang K and Wua C. Effects of Al-coagulant sludge characteristics on the efficiency of coagulants recovery by acidification. *Environmental Technology* 2012; 33: 2525-2530.
5. Wei J, Gao B, Yue Q, Wang Y, Li W and Zhu X. Comparison of coagulation behavior and floc structure characteristic of different polyferric-cationic polymer dual-coagulants in humic acid solution. *Water Research* 2009, 43, 724-732.
6. Huang X, Gao B, Rong H , Yue Q, Zhang Y and Teng P. Effect of using polydimethyldiallylammonium chloride as coagulation aid on polytitanium salt coagulation performance, floc properties and sludge reuse. *Separation and Purification Technology* 2015; 143: 64-71.
7. Zhao Y X, Gao B Y, Zhang G Z, . Qi Q B, Wang Y, Phuntsho S. Kim J-H, Shon H K and Yue Q Y. Coagulation and sludge recovery using titanium tetrachloride as coagulant for real water treatment: A comparison against traditional aluminum and iron salts, *Separation and Purification Technology* 2014; 130: 19-27.
8. Ron H, Gao B, Li R, Yue Q and Li Q. (), Effect of dose methods of a synthetic organic polymer and PFC on floc properties in dyeing wastewater coagulation process. *Environmental Technology* 2014; 35: 833-840.
9. Lee K, Morad N, Teng T, Poh B T. Reactive Dye Removal Using Inorganic-Organic Composite Material: Kinetics, Mechanism, and Optimization. *Journal of Dispersion Science and Technology* 2014; 35: 1557-1570.
10. M. Solanki., S. Suresh, S. Das, K. Shukla (2013), Treatment of real textile wastewater using coagulation technology, *International Journal of Chem. Tech. Research*, 5, 610-615.
11. D. Georgiou, A. Aivasidis, (2012), Cotton-textile wastewater management: Investigating different treatment methods, *Water Environment Research*, 84, 54-64.
12. M. Solanki, A. Dwivedi (2011), Studies on physico-chemical parameters during the treatment of waste water from viscose fiber unit by chemical coagulation, *Journal of Industrial Pollution Control*, 27, 121-126.
13. Y. Zhao., B. Gao, H. Shon, B. Cao, J. Kim, (2011), Coagulation characteristics of titanium (Ti) salt coagulant compared with aluminum (Al) and iron (Fe) salts, *Journal of Hazardous Materials*, 185, 1536-1542.
14. P.A. Moussas, A.I. Zouboulis (2008), A study on the properties and coagulation behaviour of modified inorganic polymeric coagulant – Polyferric silicate sulphate (PFSiS), *Separation and Purification Technology*, 63, 475-483.
15. L. Kos, K. Michalska, R. Żyłła, Removal of pollutants from textile wastewater using organic coagulants, *Fibres & Textiles in Eastern Europe*, 119 (6), 2016
16. DIN-38404/1 standard.
17. Hach-Lange tests no. LCK: 114, 314, 614 (Hach-Lange GmbH, Berlin, Germany).